


## **Linc Up Plus**



Connect your analogue fax-modem directly through your digital phone system—no rewiring required.

### **Key Features**

Supports incoming and outgoing analogue calls.

• Eliminates the need for dedicated phone installations or special terminal adapters.

Supports any 2-wire analogue device.

Compatible with all desktop systems with modems and communication software, and with all fax machines.

Configured for desktop or wallmount installations.

### Technically Speaking

Ordinary computer modems won't work with digital office phone systems. Unless, that is, you have a Linc Up Plus. Now you can easily, quickly, and inexpensively connect to the Internet, send and receive email and faxes, and autodial from your contact management, phone book, or communications software.

Connect the Linc Up Plus to your phone system wall jack to provide an analogue connection for virtually any analog device. There's no need for expensive dedicated phone lines, rewiring, or terminal adapters. Communication occurs over your phone system directly from your PC, Mac, or UNIX computer.

The Linc Up Plus supports full V.34 standards for transmissions up to 33,600 bps and has autodial and autoanswer capability.

Three versions are available. The Linc Up Plus–NT (MC119A) is used with Northern Telecom Meridian, Meridian 1 (option 11 to 81), SL-1, or SL-100 and Norstar (not compatible with M2216 acd) phones. The Linc Up Plus–ATT (MC120A) is used with current AT&T, Lucent Definity phones, and System 75/85. And the Linc Up Plus–RLM (MC121A) is for Siemens ROLM CBX phone sets. All three models can also be used as a standalone interface typical for a fax installation.

Additional features include:

- Supports full-duplex speakerphone functions found on today's fax modems and teleconferencing units.
- Shares the same port number as the existing phone; no additional port needed.
- Maintains normal phone operation when the fax or modem is on-hook.
- Factory configurable for ulaw (U.S.) or A-law mode.

#### **Specifications**

- Standards Supports V.34
- **Speed** Up to 33,600 bps
- Compliance UL®, FCC, CSA

Connection — MC119AE: Requires standard digital Northern Telecom<sup>®</sup> wall jack; MC120AE: Requires standard AT&T<sup>®</sup> or Lucent wall jack; MC121AE: Requires standard ROLM<sup>®</sup> wall jack Power — 18 VAC adapter, available in 110 VAC (220-VAC models available)

**Size** — 18.8 x 9.9 x 4.6 cm

Weight — 482 g

# **Ordering Information**

PRODUCT NAME	ORDER CODE
Linc Up Plus	
NT	MC119AE
ATT	MC120AE
RLM	MC121AE