




BLACK BOX[®]

NETWORK SERVICES

© 2004. All rights reserved.
Black Box Corporation.

Black Box Network Services • 464 Basingstoke Road • Reading, Berkshire, RG2 0BG • Tech Support: 0118 965 6000 • www.blackbox.co.uk • e-mail: techhelp@blackbox.co.uk

PALM-SIZED ETHERNET SWITCHES



Our popular Ethernet switches are now available with a fibre uplink!

Key Features

- ▶ **Compact size saves valuable space.**
- ▶ **Plug-and-play.**
- ▶ **10-/100-Mbps copper ports are autosensing for speed, duplex, and MDI/MDI-X.**
- ▶ **Full wire-speed forwarding.**
- ▶ **Nonblocking switch architecture is ideal for video and data-intensive applications.**
- ▶ **Choose from 5- or 8-port copper-only models or from models with 7 copper ports and a port with an ST[®] or SC fibre uplink.**

Economically expand your small-company or workgroup network with a tiny device that fits in the palm of your hand. The Palm-Sized Ethernet Switch and Palm-Sized Ethernet Switch for Fibre enable you to integrate legacy 10-Mbps networks with 100-Mbps Fast Ethernet. The switches also function as bridges to extend the distance between two 100-Mbps network segments.

The Palm-Sized Ethernet Switch is available as a 5- or 8-port model. All RJ-45 ports are autonegotiating for 10BASE-T/100BASE-TX.

The Palm-Sized Ethernet Switch for Fibre is available with eight ports only. Seven ports feature RJ-45 connectors, and they are autonegotiating for 10BASE-T/100BASE-TX. The eighth port features either an ST or SC connector that provides a

100-Mbps fibre uplink that's perfect for connecting workgroups to fibre backbones. It can even be used for links between nodes up to 2 kilometres (1.2 mi.) apart.


Both switches support the most demanding multimedia and imaging applications, thanks to their nonblocking switching architecture. You can run 10- and 100-Mbps speed and half- or full-duplex transmission modes on the same port.

What's more, the Palm-Sized Ethernet Switch and Palm-Sized Ethernet Switch for Fibre enable full-wire speed forwarding. They also provide back pressure and IEEE 802.3x-compliant flow control. The switches comply with other Ethernet standards, too, including IEEE 802.3 for 10BASE-T and IEEE 802.3u for 100BASE-TX and 100BASE-FX.

All switches include an internal CPU chip that provides auto-MDI/MDI-X capability on all mixed Ethernet ports. The chip also supports a MAC address table for 2000 addresses and a 1-MB shared port buffer.

The Palm-Sized Ethernet Switch and Palm-Sized Ethernet Switch for Fibre come with an external, autosensing power supply that includes a kit of three separate and detachable AC power adapters—a 2-prong adapter for US, a 3-prong adapter for UK, and a 2-post adapter for continental Europe. An L-shaped tool is also included that enables you to remove one adapter so another can be installed. Each adapter is mounted on a plastic base that slides into and out of the power supply.

A Palm-Sized Ethernet Switch supports a small office network.



Specifications

Approvals: FCC Part 15 Class B, CE, VCCI Class B

Distance (Maximum):
 LB8405A-R3, LB8408A-R3:
 100 m (328 ft.) using 10BASE-T UTP Category 3, 4, 5 cable or 100BASE-TX UTP Category 5 or 5e cable;
 LB8418A-ST, LB8418A-SC: 2 km (1.2 mi.) over fibre for links between nodes

Duplex Support: Half- and full-duplex, autonegotiating

Ethernet Standards:

All: 10BASE-T: IEEE 802.3;
 100BASE-TX: IEEE 802.3u;
 LB8418A-ST, LB8418A-SC:
 100BASE-FX: IEEE 802.3u

Forwarding Rate:

10 Mbps: 14,880 pps;
 100 Mbps: 148,800 pps

MAC Addresses: 2000

Switching Method:
 Store and forward

Connectors:
 LB8405A-R3: (5) RJ-45;

LB8408A-R3: (8) RJ-45;
 LB8418A-ST: (7) RJ-45, (1) pair ST;
 LB8418A-SC: (7) RJ-45, (1) pair SC

Indicators: LEDs:

Per unit: (1) Power;
 Per port: (1) LNK/ACT

Temperature Tolerance:

Operating: 32 to 104°F (0 to 40°C);
 Storage: -13 to +158°F (-25 to +70°C)

Relative Humidity:
 10 to 90% noncondensing

Power: 100–240 VAC, 50–60 Hz, autosensing, external;
 12 VDC output;
 7.2 W (maximum) power consumption

Size: LB8405A-R3, LB8408A-R3:
 0.8"H x 5.2"W x 4.5"D (2 x 13.2 x 11.4 cm);
 LB8418A-ST, LB8418A-SC:
 1.1"H x 6.3"W x 3.2"D (2.8 x 16 x 8.1 cm)

Weight: 0.9 lb. (0.4 kg)

What the Package Includes

- (1) Palm-Sized Ethernet Switch
- (1) data sheet
- (1) CD that includes a users' manual
- (4) rubber feet
- (1) wallmount power supply that includes: (3) power adapters for US, UK, and continental Europe; and (1) L-shaped tool for removing any power adapter so another type can be installed

Ordering Information

ITEM	CODE
Palm-Sized Ethernet Switch for Fibre	
ST®	LB8415A-ST
SC.....	LB8418A-SC
<i>For optimum performance, order...</i>	
GigaBase® 350 CAT5e Patch Cable, 4-Pair, Beige, Straight-Pinned, PVC, 3.0-m.....	EVNSL85-0010
Ceramic Terminated Multimode Fibre Optic Cables, Duplex, Riser	
ST-ST	EFN062-CC
SC-SC	EFN4025