



BLACK BOX[®]

NETWORK SERVICES

16/24 Ports Nway Fast Ethernet Switch plus 1-100Mbps FO-Slot



Key Features

- ▶ 16/24 Port 10/100 BASE-T/TX Nway Fast Ethernet Switch.
- ▶ 1-FO module port (100BASE-FX).
- ▶ Smart Plug & Play Device, Easy for Installation and Use.
- ▶ Full / Half Duplex Capabilities.
- ▶ Full Wire Speed Filtering / Forwarding Rates.
- ▶ Store & Forward Switching Methods.
- ▶ Compact Rigid Rackmount Size.
- ▶ Provides Non-Blocking and Non-Head-Of-Line Blocking.
- ▶ Supports Auto-Detect of Full/Half Duplex Modes in All Ports.
- ▶ Supports Broadcast Storm Protection.
- ▶ Supports Auto MDIX Crossover Capabilities.
- ▶ One Uplink Port.
- ▶ Provided reset button.
- ▶ One Trunking up to 800Mbps Link. (4 Ports At Full-duplex).
- ▶ Support link Fault Tolerance On Trunking Port.
- ▶ The Port Based on V-LAN Support for up to 4 Groups.
- ▶ The Port Setting for Nway or Force Mode Operation .

The Switches LBS216AE-R2 and LBS224AE-R3 provide 16 or 24 10/100Mbps ports and one 100Mbps Slot. This Switch Family was designed for easy installation and high performance in an environment where traffic on the network and the number of user increase continuously.

The compact Rack-mount size was specifically designed for ROBO (Remote Office & Branch Office) and medium to large workgroups and can be installed where space is limited; moreover it provides smooth network migration and easy upgrade to network capacity.

Specifications

Standards Compliance —

IEEE 802.3 10BASE-T, IEEE 802.3u
100BASE-TX

Number Of Ports — 16/24 ports:
10/100Mbps Nway port

Expansion Interface — 1 uplink port

Fully Flow Control Supported —

Half-duplex mode: Backpressure, Full-
duplex mode: IEEE 802.3x

Network Transmission Media —

10BASE-T Cat. 3, 4, 5 UTP/STP,
100BASE-TX Cat. 5 UTP/STP

Network Status Monitoring

LEDs — per port: LINK/ACT, 10/100M,
FDX, System: POWER

Buffer Memory — RAM: 4Mbits per
device, RAM buffer dynamically allocated
for each port

Filter/Forward Rate — Packet
Filtering/ Forwarding Rates, 100Mbps
port - 148,800pps, 10Mbps port -
14,880pps

MAC Address — up to 2K per device
Power Supply - 90-260V/AC, 50-60Hz

Power Consumption —

16 Watts (Max)

Temperature —

Operating: 0°C ~ 60°C
Storage: -20°C ~ +90°C

Humidity — 10% ~90% RH (Non-con-
densing)

Dimension —

LxWxH 440mm x 220mm x 44mm

Weight - 2.9Kg

Safety & EMI Certificates — CE &

FCC-A

Ordering information

ITEM

CODE

Switch 16x10/100Mbps	LBS216AE-R2
Switch 24x10/100Mbps	LBS224AE-R3

Black Box Network Services - The world's largest network services company

We are, with 25 years of experience, the
world leader in network infrastructure
services.

On the Phone — no charge, answer
calls in less than 20 seconds, find the
right product with our technical experts.

On-site — superior design and engi-
neering, Certified installations, end-to-
end service.

On-line — receive technical knowledge
on-line, including technology overviews,
BLACK BOX Explains and the Knowledge
Box.

**Most comprehensive TECHNICAL
SUPPORT** — our best Product! Free
hotline TECH SUPPORT!

**The world's best customer
service** — Custom design services
and products, the best warranties,
money-saving discount programs.

BLACK BOX exclusives —
Certification Plus. Guaranteed-for-life
products and services.