




# BLACK BOX<sup>®</sup>

## NETWORK SERVICES

### ServSensor Contact



#### Key Features

- ▶ Supports up to 8 plug-and-play sensors
- ▶ 20 or 60 dry contact inputs
- ▶ Email warnings and alarms / SNMP traps
- ▶ Java-based web user interface

#### Product description

ServSensor Contact is based on Black Box's popular ServSensor product with an additional 20 or 60 dry contact inputs. It comes in a 1U (20 contacts version) or 2U (60 contacts version) 19-inch rack-mountable robust metallic enclosure.

At the core of the unit is the ServSensor, which is enhanced with the 20 / 60 dry contact system. This offers support for remote monitoring and management of various external devices. This integrated system enables connection and monitoring of devices like HVAC systems, Security Equipment, UPS, Generators, Industrial Equipment etc. The embedded web server makes the addition of these devices easy.

ServSensor Contact comes with 8 full auto-sense RJ-45 ports for connecting any of the intelligent sensors from the ServSensor product line. An additional 20 (60), 2 wire dry contact ports are provided giving a total of up to 28 (68) dry contact ports. The specially designed 2

wire dry contact ports are easy to use and allow you to make your own dry contact cables quickly and easily.

ServSensor Contact is a completely embedded host and comes with a proprietary Linux-like operating system. It is equipped with a TCP/IP stack, internal web Server, e-mail, SMS and full SNMP functionality. It is virtually a 'plug-n-play' device and is extremely easy to use and maintain. The installation process is also simple and one does not need additional power supply or batteries when new optional sensors are added.

You can connect up to 8 of intelligent, auto-sense sensors in any combination to monitor temperature, humidity, water leakage and airflow including long term graphing, security, detection of AC power line voltage, measurement of DC voltage, control relays, and many more such uses. An integrated data collection and graphing package is especially useful in spotting trends and providing information for analysis.

The new improved web interface gives you the freedom to configure the dry contacts and setting the alarms to keep you informed. The embedded database has an in-built time stamp that maintains a log of all events. The product is fully embedded with SNMP, which means a tightly integrated solution for integrating with any of your SNMP based network management systems.

The ServSensor Contact's advanced encrypted micro code updating program can easily and effectively update your firmware over the network.

# Specifications

Sensors: (8) RJ45 F, proprietary signaling; EME11\*A-20: (20), EME11\*A-60: (60) terminal screw-compatible dry contacts  
 Serial: (1) RJ45 F RS232/V.34  
 Network: (1) RJ45 F 10BASE-T/100BASE-TX autosense  
 Power: (1) 2.4 mm jack F

### Engine

#### Specifications:

Processor: AVR 8-Bit Risc  
 Memory: 128kB Flash, 32kB internal RAM  
 Operating system: proprietary

#### Feature:

- sensor measurement and graphing (day, week, month, year)
- configurable low / high warning and critical levels
- email alerts, SNMP traps

### Management

Indicators: (1) Power, (1) Link, (1) Activity, (8) Status, (8) Online; per dry contact input: (1) Status, (1) Online  
 Configuration and control: HTTP  
 Protocols supported (client): DHCP, DNS, SMTP, (S)NTP, SNMPv1  
 Access control and security: admin / user access levels, password

### Physical and environmental

Power supply: external; Input: 100 – 240 V AC 47 – 63 Hz auto sense; Output: 7.5 V DC, max. 2 A  
 Operating temperature range: -35 ... +55 °C  
 Operating temperature humidity: 20 – 80%RH, non-condensing  
 Operating altitude: 0 – 3000 m  
 Dimensions (H x W x D):  
 EME11\*A-20: 42 x 457 x 127 mm,  
 EME11\*A-60: 88 x 457 x 127 mm  
 Weight: EME11\*A-20: 1 kg,  
 EME11\*A-60: 2 kg  
 MTBF: 87'600 h

<hr>

## Ordering information

| ITEM  | CODE        |
|---|-------------|
| Contact-20 8-Port 20 dry contacts no sensor                         | EME111A-20  |
| Contact-20 8-Port 20 dry contacts 1x temp. sensor                   | EME112A-20  |
| Contact-20 8-Port 20 dry contacts 1x dual (temp. & humidity) sensor | EME113A-20  |
| Contact-60 8-Port 60 dry contacts no sensor                         | EME111A-60  |
| Contact-60 8-Port 60 dry contacts 1x temp. sensor                   | EME112A-60  |
| Contact-60 8-Port 60 dry contacts 1x dual (temp. & humidity) sensor | EME113A-60  |
| <b>Sensors</b>  |             |
| Temperature sensor 4.5m   | EME1T1-015  |
| Dual temperature and humidity sensor 4.5m                           | EME1TH1-015 |
| Motion detector sensor 4.5m   | EME1M1-015  |
| Security sensor 4.5m  | EME1Y1-015  |
| Dry contact sensor 4.5m   | EME1K1-015  |
| Power Switch 1-port 0.9m  | EME1P1-003  |

## Black Box Network Services - The world's largest network services company

We are, with 25 years of experience, the world leader in network infrastructure services.

**On the Phone** — no charge, answer calls in less than 20 seconds, find the right product with our technical experts.

**On-site** — superior design and engineering, Certified installations, end-to-end service.

**On-line** — receive technical knowledge on-line, including technology overviews, Black Box Explains and the Knowledge Box.

**Most comprehensive TECHNICAL SUPPORT** — our best Product! Free hotline TECH SUPPORT!

**The world's best customer service** — Custom design services and products, the best warranties, money-saving discount programs.

**BLACK BOX exclusives** — Certification Plus. Guaranteed-for-life products and services.