

Table 6. DB-25 Pin Connection V.24/RS-232

Pin	Name	Type
1	SHIELD	
2	TxD	Output
3	RxD	Input
4	RTS	Output
5	CTS	Input
6	BAUD2	Input
7	GND	
8	BAUD1	Input
9	NC	
10	NC	
11	NC	
12	NC	
13	NC	
14	NC	
15	TCLK/EXCLK	Input
16	NC	
17	RCLK/BAUD0	Input
18	NC	
19	NC	
20	NC	
21	NC	
22	ACCM	Input
23	NC	
24	NC	
25	NC	

Table 7. DB-25 Pin Connection V.35

Pin	Name	Type
1	SHIELD	
2	TxD-A	Output
3	RxD-A	Input
4	RTS-A	Output
5	CTS-A	Input
6	BAUD2	Not used
7	GND	
8	BAUD1	Not used
9	RCLK-B	Input
10	NC	
11	NC	
12	TCLK-B/EXCLK-B	Input
13	NC	
14	TxD-B	Output
15	TCLK-A/EXCLK-A	Input
16	RxD-B	Input
17	RCLK-A	Input
18	NC	
19	NC	
20	NC	
21	NC	
22	ACCM	Input
23	NC	
24	NC	
25	NC	

**Table 8. DB-25 Pin Connection V.11
(used for RS-530, X.21, V.36)**

Pin	Name	Type
1	SHIELD	
2	TxD-A	Output
3	RxD-A	Input
4	RTS-A	Output
5	CTS-A	Input
6	BAUD2	Not used
7	GND	
8	BAUD1	Not used
9	RCLK-B	Input
10	NC	
11	NC	
12	TCLK-B/EXCLK-B	Input
13	CTS-B	Input
14	TxD-B	Output
15	TCLK-A/EXCLK-A	Input
16	RxD-B	Input
17	RCLK-A	Input
18	NC	
19	RTS-B	Output
20	NC	
21	NC	
22	ACCM	Input
23	NC	
24	NC	
25	NC	